




High Intensity Mixer

STANDARD FEATURES

- Removable And Fixed Deflector
- Hinged or Swivel Lid
- Variant Tool Design
- Hinged Access Cover
- Customized Lid Openings
- Multiple Temperature Sensors

AVAILABLE FEATURES & OPTIONS

- Mirror Finish Interior
- Swing Away Discharge
- Split Bowl Design
- Sample and View Port
- VFD with PLC Control Panel
- Recipe Storage



Contact Us

Website: reliancemixers.com

Address: 1900 FM 1092
Missouri City, Tx 77459

Email: sales@reliancemixers.com

Custom Mixers for Custom Needs!



ADDITIONAL FEATURES & OPTIONS

- Sample Ports
- Vibrations Sensors
- Thicker Bowl Walls for longer life
- Easy Clean Features
- Large Discharge for faster Cycle Time
- Mirror Finished Stainless Steele Exterior
- Economy Series Mixer to meet budgetary needs

Model	Total Capacity		Operating Capacity		Batch Size		Motor Size
	Liters	Cu.Ft.	Liters	Cu.Ft.	Kgs.	Lbs.	H.P.
VFM-10	10.0	0.4	8.0	0.3	4.1	9.0	5.0
VFM-40	40.0	1.4	32.0	1.1	16.3	36.0	15
VFM-75	75.0	2.6	60.0	2.1	30.6	67.5	25
VFM-100	100.0	3.5	80.0	2.8	40.8	90.0	30
VFM-200	200.0	7.0	160.0	5.6	81.6	180.0	60
VFM-350	350.0	12.4	280.0	9.9	142.9	315.0	100
VFM-500	500.0	17.7	400.0	14.1	204.1	450.0	125
VFM-600	600.0	21.2	480.0	17.0	244.9	540.0	150
VFM-800	800.0	28.3	640.0	22.6	326.6	720.0	250
VFM-1000	1000.0	35.3	800.0	28.2	408.2	900.0	350
VFM1200	1200.0	42.4	960.0	33.9	489.9	1080.0	400
VFM-1500	1500.0	53.0	1200.0	42.4	612.3	1350.0	450
VFM-2000	2000.0	70.6	1600.0	56.5	816.5	1800.0	700
VFM-2500	2500.0	88.25	2000.0	70	1,027	2260.0	800

Batch size and HP requirements vary with the bulk density (32 lbs./cu.ft. used for tables)



Contact Us

Website: reliancemixers.com

Address: 1900 FM 1092
Missouri City, Tx 77459

Email: sales@reliancemixers.com

