



REMOVABLE CONTAINER MIXERS RC SERIES



- 18 month warranty
- 24-hour technical support

Clamps



- Pneumatically operated cam type clamps
- Low maintenance

Hopper Lifting Mechanism




 Two pneumatic cylinders lift the hopper into the clamping position

Injection Ports



- Nitrogen purge helps create an inert and controlled mixing environment
- Liquid injection allows for thorough distribution during mixing cycle



**Batch size and HP reqirements may vary with the bulk density (32 lbs./cu.ft. used for tables)

Standard Features

- Air purge shaft seals
- Jacketed mixing head
- Venting device
- Controls for each operation
- Temperature sensors
- Rigid dual pedestal construction
- Variable frequency drives
- Highly polished mixing head at container
- Precise rotation of mixing head as controlled by optical encoder

Available Options

Touch screen controls

Allows for recipe storage. Operator simply enters recipe number/name and all operating parameters are automatically loaded.

Jacketed containers

Allows for cooling medium to circulate throughout the hopper during the mixing process.

Dual independent drives
 Each mixing tool is independently driven, allowing for infinite speed combinations.

Mixer Accessories

- Dust Free Charging And Discharging Stations
- Automated Cleaning Station















GENERAL APPLICATION	INDUSTRY
 Homogenized & Heated Mixing Drying & Degassing Fusing Surface Coloring Densifying Agglomerating Grinding & Pulverizing Dissolving & Melting Preparation of Master Batches 	 Plastic Processing Powder Coating and Toner Food and Pharmaceutical Cosmetics Liquid Paints Rubber Wood Composites Chemical



RELIANCE INDUSTRIES

1900 FM 1092 Missouri City, Texas 77459

PH: 281-499-9926 / (800) 353-0472 / FAX: 281-499-4308

www.reliancemixers.com EMAIL: sales@reliancemixers.com